

Nominal heat output [kW]

Appliances properties: Wodtke GmbH - HK 02

Master data

Date of entryJan 14, 2009ManufacturerWodtke GmbHModelHK 02

Continuous burning appliance

Type test standard DIN 18895
Year of testing 1989

Test laboratory RRF Rhein-Ruhr-Feuerstättenprüfstelle GmbH

11

Number of test laboratory 2

Number of test report 95 89 28



Flue gas values

	Wood	
Flue gas mass flow [g/s]	16	
Flue gas mass flow [g/s]	362	
Necessary flue draught [Pa]	10	

Further important characteristics of the appliance

Suitability for installation to a shared flue 1)

Connectivity to the central heating system

General technical approval for room sealed operation

On behalf of the manufacturer, the HKI Industrieverband e.V. hereby confirms compliance with the respective requirements* in accordance with 1.BImSchV. The type test report of the fireplace has been submitted to the HKI Industrieverband e.V.

¹⁾ For unsealed operation it is possible to install the appliances to a shared flue system (please see installation manual).

^{*} A green check mark with a "1" indicates that the requirements of the 1st BImSchV are fulfilled, a green check mark with a "2" indicates that the 2nd level of the 1st BImSchV is fulfilled. A yellow check mark shows that the transitional regulation of the 1st BImSchV is fulfilled and a red line means that the 1st BImSchV is not fulfilled.

Norm: Inset appliances (with closed firedoor) D - 1.BImSchV According to the transitional rule §26 the appliance can be used until 31.12.2020 F - Crédit d'impôt à la transition énergétique

Evaluation of emission data and efficiency Lignite briquettes

Norm : Inset appliances (with closed firedoor) Evaluation

D - 1.BlmSchV

According to the transitional rule §26 the appliance can be used until 31.12.2020



No symbol means that there are no requirements.

No measuring values are available for this fuel, operation with this fuel is not permitted

Here you will find further information

No information/unknown