

Appliances properties: Bernhard Kaschütz GmbH - Firetherm 6 mit 1 Nachheizkasten

anufacturer bedel Fire cominal heat output [kW] coclared nominal space heating output [kW] firtial load [kW] 3.3 continuous burning appliance ermal output pe test standard car of testing st laboratory were sumber of test laboratory Ber 6.6 6.7 6.8 7 8.8 8.8 8.9 8.9 8.9 8.9 8.9		
ordel Fire ominal heat output [kW] 6.6 ordared nominal space heating output [kW] 6 ortial load [kW] 3.3 ortinuous burning appliance overmal output	therm 6 mit 1 Nachheizkasten EN 13229	
ominal heat output [kW] 6.6 cclared nominal space heating output [kW] 6 critial load [kW] 3.3 continuous burning appliance cermal output pe test standard DIN car of testing 201 st laboratory Ver umber of test laboratory 8	EN 13229	
cclared nominal space heating output [kW] 6 artial load [kW] 3.3 antinuous burning appliance eermal output pe test standard DIN aar of testing 201 st laboratory Verumber of test laboratory 8	5	
artial load [kW] 3.3 continuous burning appliance dermal output	5	
portinuous burning appliance dermal output pe test standard par of testing st laboratory Uer Jumber of test laboratory 8	5	
pe test standard DIN par of testing 201 st laboratory Ver umber of test laboratory 8	5	
pe test standard DIN ear of testing 201 st laboratory Ver umber of test laboratory 8	5	
st laboratory Verumber of test laboratory 8	5	
st laboratory Ver umber of test laboratory 8		
umber of test laboratory 8	ovek a ved Farakversanskik der Hefran Österniska	
•	Versuchs- und Forschungsanstalt der Hafner Österreichs	
umber of test report VH	8	
	F-15-006-P	
lue gas values		
	Wood	
ue gas mass flow [g/s]	43.5	
ue gas mass flow [g/s]	169.5	
ecessary flue draught [Pa]	12.5	

Further important characteristics of the appliance

Suitability for installation to a shared flue¹⁾

Connectivity to the central heating system

General technical approval for room sealed operation

On behalf of the manufacturer, the HKI Industrieverband e.V. hereby confirms compliance with the respective requirements* in accordance with 1.BImSchV. The type test report of the fireplace has been submitted to the HKI Industrieverband e.V.

¹⁾ For unsealed operation it is possible to install the appliances to a shared flue system (please see installation manual).

^{*} A green check mark with a "1" indicates that the requirements of the 1st BImSchV are fulfilled, a green check mark with a "2" indicates that the 2nd level of the 1st BImSchV is fulfilled. A yellow check mark shows that the transitional regulation of the 1st BImSchV is fulfilled and a red line means that the 1st BImSchV is not fulfilled.

Evaluation of emission data and efficiency Wood

Norm : Inset appliances (with closed firedoor)	Evaluation
D - 1.BlmSchV	Stufe 2
A - Austrian regulation referred to Art 15a B-VG	2015
CH - Swiss clean air act	✓
DK - Danish regulation for air pollution from wood burners	✓
F - Crédit d'impôt à la transition énergétique	√ 7 ☆

Evaluation of emission data and efficiency Lignite briquettes

Norm : Inset appliances (with closed firedoor)	Evaluation
D - 1.BImSchV	
DK - Danish regulation for air pollution from wood burners	I



No symbol means that there are no requirements.

No measuring values are available for this fuel, operation with this fuel is not permitted

Here you will find further information

No information/unknown