

Appliances properties: HOXTER a.s. - ECKA 60/35/50 SLh

Date of entry Manufacturer Model ECKA 60/35/50 SLh Nominal heat output [kW] 7 Continuous burning appliance Type test standard DIN EN 13229 Year of testing 2019 Test laboratory Number of test laboratory Number of test report Flue gas values Flue gas mass flow [g/s] Necessary flue draught [Pa] Oct 26, 2021 HOXTER a.s. HOXTER	Master data			
Manufacturer Model ECKA 60/35/50 SLh Nominal heat output [kW] 7 Continuous burning appliance Type test standard DIN EN 13229 Year of testing 2019 Test laboratory Number of test laboratory Number of test report Flue gas values Wood Flue gas mass flow [g/s] Flue gas mass flow [g/s] Necessary flue draught [Pa] HOXTER a.s. HOXTER a.s. ECKA 60/35/50 SLh 7 Wood Strojiensky Zkusebni Ustav s.p. Wood Wood Flue gas mass flow [g/s] 7.3 Flue gas mass flow [g/s] 10	Date of entry	Oct 26, 2021		
Model Nominal heat output [kW] 7 Continuous burning appliance Type test standard Year of testing 2019 Test laboratory Number of test laboratory Number of test report Flue gas walues Wood Flue gas mass flow [g/s] Flue gas mass flow [g/s] Necessary flue draught [Pa] ECKA 60/35/50 SLh 7 Wood ECKA 60/35/50 SLh 7 The Continuous burning appliance UNIVED TO				
Nominal heat output [kW] Continuous burning appliance Type test standard DIN EN 13229 Year of testing 2019 Test laboratory Strojirensky Zkusebni Ustav s.p. Number of test laboratory 19 Number of test report Strojirensky Zkusebni Ustav s.p. Wood Flue gas values Wood Flue gas mass flow [g/s] Flue gas mass flow [g/s] Necessary flue draught [Pa] 10				
Continuous burning appliance Type test standard DIN EN 13229 Year of testing 2019 Test laboratory Strojirensky Zkusebni Ustav s.p. Number of test laboratory 19 Number of test report Strojirensky Zkusebni Ustav s.p. Wood Flue gas values Wood Flue gas mass flow [g/s] Flue gas mass flow [g/s] Necessary flue draught [Pa] DIN EN 13229 2019 Strojirensky Zkusebni Ustav s.p. Wood Tusting the flue gas mass flow [g/s] 7.3 Flue gas mass flow [g/s] 10				
Year of testing Test laboratory Strojirensky Zkusebni Ustav s.p. Number of test laboratory 19 Number of test report 30-14266/2/T Flue gas values Wood Flue gas mass flow [g/s] Flue gas mass flow [g/s] Necessary flue draught [Pa] 10		_		
Test laboratory Number of test laboratory Number of test report Strojirensky Zkusebni Ustav s.p. 19 Number of test report 30-14266/2/T Flue gas values Wood Flue gas mass flow [g/s] Flue gas mass flow [g/s] Necessary flue draught [Pa] Strojirensky Zkusebni Ustav s.p. Wood 19 Number of test laboratory 19 No-14266/2/T 10	Type test standard	DIN EN 13229		
Number of test laboratory Number of test report 30-14266/2/T Flue gas values Wood Flue gas mass flow [g/s] Flue gas mass flow [g/s] 17.3 Flue gas mass flow [g/s] 10	Year of testing	2019		
Number of test report 30-14266/2/T Flue gas values Wood Flue gas mass flow [g/s] 7.3 Flue gas mass flow [g/s] Necessary flue draught [Pa] 10	Test laboratory	Strojirensky Zkusebni Ustav s.p.		
Flue gas values Wood Flue gas mass flow [g/s] Flue gas mass flow [g/s] Necessary flue draught [Pa] 10	Number of test laboratory	19		
Flue gas mass flow [g/s] Flue gas mass flow [g/s] Flue gas mass flow [g/s] Necessary flue draught [Pa] Wood 7.3 Flue gas mass flow [g/s] 10	Number of test report	30-14266/2/T		
Flue gas mass flow [g/s] Flue gas mass flow [g/s] Flue gas mass flow [g/s] Necessary flue draught [Pa] Wood 7.3 Flue gas mass flow [g/s] 10				
Flue gas mass flow [g/s] Flue gas mass flow [g/s] Necessary flue draught [Pa] 7.3 227 No 10	Flue gas values			
Flue gas mass flow [g/s] Necessary flue draught [Pa] 10			Wood	
Necessary flue draught [Pa] 10	Flue gas mass flow [g/s]		7.3	
	Flue gas mass flow [g/s]		227	
Further important characteristics of the appliance	Necessary flue draught [Pa]		10	
Further important characteristics of the appliance				
Further important characteristics of the appliance				
	Further important characteristics of the appliance			

Suitability for installation to a shared flue 1)

Connectivity to the central heating system

General technical approval for room sealed operation

On behalf of the manufacturer, the HKI Industrieverband e.V. hereby confirms compliance with the respective requirements* in accordance with 1.BImSchV. The type test report of the fireplace has been submitted to the HKI Industrieverband e.V.

¹⁾ For unsealed operation it is possible to install the appliances to a shared flue system (please see installation manual).

^{*} A green check mark with a "1" indicates that the requirements of the 1st BImSchV are fulfilled, a green check mark with a "2" indicates that the 2nd level of the 1st BImSchV is fulfilled. A yellow check mark shows that the transitional regulation of the 1st BImSchV is fulfilled and a red line means that the 1st BImSchV is not fulfilled.

Evaluation of emission data and efficiency Wood

Norm : Inset appliances (with closed firedoor)	Evaluation
D - 1.BlmSchV	Stufe 2
A - Austrian regulation referred to Art 15a B-VG	2015
CH - Swiss clean air act	✓
DK - Danish regulation for air pollution from wood burners	✓
F - Crédit d'impôt à la transition énergétique	√ 7 ☆

Evaluation of emission data and efficiency Lignite briquettes

Norm : Inset appliances (with closed firedoor)	Evaluation
D - 1.BImSchV	
DK - Danish regulation for air pollution from wood burners	I



No symbol means that there are no requirements.

No measuring values are available for this fuel, operation with this fuel is not permitted

Here you will find further information

No information/unknown