

## Appliances properties: Spartherm Feuerungstechnik GmbH - Varia 1V H2O 9,0 kW - A1 (ab 01.2014)

Master data  Date of entry  Manufacturer  Spartherm Feuerungstechnik GmbH  Varia 1V H2O 9,0 kW - A1 (ab 01.2014)  Nominal heat output [kW]  9  Continuous burning appliance  Type test standard  DIN EN 13229  Year of testing  2013  Test laboratory  RRF Rhein-Ruhr-Feuerstättenprüfstelle GmbH  Number of test laboratory  Number of test report  RRF - 29 13 3358  Flue gas mass flow [g/s]  Flue gas mass flow [g/s]  Flue gas mass flow [g/s]  Necessary flue draught [Pa]	
Manufacturer  Model  Varia 1V H2O 9,0 kW - A1 (ab 01.2014)  Nominal heat output [kW]  9  Continuous burning appliance  Type test standard  Year of testing  Test laboratory  Number of test laboratory  Number of test report  Flue gas mass flow [g/s]  Flue gas mass flow [g/s]  Necessary flue draught [Pa]  Further important characteristics of the appliance	
Manufacturer  Model  Varia 1V H2O 9,0 kW - A1 (ab 01.2014)  Nominal heat output [kW]  9  Continuous burning appliance  Type test standard  Year of testing  2013  Test laboratory  Number of test laboratory  Number of test report  Flue gas mass flow [g/s]  Flue gas mass flow [g/s]  Flue gas mass flow [g/s]  Further important characteristics of the appliance  Further important characteristics of the appliance	
Model  Nominal heat output [kW]  Continuous burning appliance  Type test standard  DIN EN 13229  Year of testing  2013  Test laboratory  RRF Rhein-Ruhr-Feuerstättenprüfstelle GmbH  Number of test laboratory  2  Number of test report  RRF - 29 13 3358  Flue gas walues  Flue gas mass flow [g/s]  Flue gas mass flow [g/s]  Necessary flue draught [Pa]	
Nominal heat output [kW]  Continuous burning appliance  Type test standard  DIN EN 13229  Year of testing  2013  Test laboratory  RRF Rhein-Ruhr-Feuerstättenprüfstelle GmbH  Number of test laboratory  2  Number of test report  RRF - 29 13 3358  Flue gas values  Flue gas mass flow [g/s]  Flue gas mass flow [g/s]  Necessary flue draught [Pa]	
Type test standard  DIN EN 13229  Year of testing  2013  Test laboratory  RRF Rhein-Ruhr-Feuerstättenprüfstelle GmbH  Number of test laboratory  2  Number of test report  RRF - 29 13 3358  Flue gas mass flow [g/s]  Flue gas mass flow [g/s]  Necessary flue draught [Pa]  Further important characteristics of the appliance	
Year of testing  Test laboratory  RRF Rhein-Ruhr-Feuerstättenprüfstelle GmbH  Number of test laboratory  RRF - 29 13 3358  Flue gas values  Flue gas mass flow [g/s]  Flue gas mass flow [g/s]  Necessary flue draught [Pa]  Further important characteristics of the appliance	
Year of testing  Test laboratory  RRF Rhein-Ruhr-Feuerstättenprüfstelle GmbH  Number of test laboratory  RRF - 29 13 3358  Flue gas values  Flue gas mass flow [g/s]  Flue gas mass flow [g/s]  Necessary flue draught [Pa]  Further important characteristics of the appliance	
Test laboratory RRF Rhein-Ruhr-Feuerstättenprüfstelle GmbH Number of test laboratory 2 RRF - 29 13 3358  Flue gas walues  Flue gas mass flow [g/s] Flue gas mass flow [g/s] Necessary flue draught [Pa]	
Number of test report  RRF - 29 13 3358  Flue gas values  Flue gas mass flow [g/s] Flue gas mass flow [g/s] Necessary flue draught [Pa]  Further important characteristics of the appliance	
Flue gas mass flow [g/s] Flue gas mass flow [g/s] Flue gas mass flow [g/s] Necessary flue draught [Pa]  Further important characteristics of the appliance	
Flue gas mass flow [g/s] Flue gas mass flow [g/s] Flue gas mass flow [g/s] Necessary flue draught [Pa]  Further important characteristics of the appliance	
Flue gas mass flow [g/s] Flue gas mass flow [g/s] Necessary flue draught [Pa]  Further important characteristics of the appliance	
Flue gas mass flow [g/s]  Necessary flue draught [Pa]  Further important characteristics of the appliance	
Flue gas mass flow [g/s]  Necessary flue draught [Pa]  Further important characteristics of the appliance	Wood
Necessary flue draught [Pa]  Further important characteristics of the appliance	7.9
Further important characteristics of the appliance	234
	12
Suitability for installation to a shared flue <sup>1)</sup>	<b>~</b>
Connectivity to the central heating system	•

<sup>1)</sup> For unsealed operation it is possible to install the appliances to a shared flue system (please see installation manual).

General technical approval for room sealed operation

On behalf of the manufacturer, the HKI Industrieverband e.V. hereby confirms compliance with the respective requirements\* in accordance with 1.BImSchV. The type test report of the fireplace has been submitted to the HKI Industrieverband e.V.

<sup>\*</sup> A green check mark with a "1" indicates that the requirements of the 1st BImSchV are fulfilled, a green check mark with a "2" indicates that the 2nd level of the 1st BImSchV is fulfilled. A yellow check mark shows that the transitional regulation of the 1st BImSchV is fulfilled and a red line means that the 1st BImSchV is not fulfilled.

orm : Inset appliances (with closed firedoor)	Evaluation
- 1.BlmSchV	Stufe 2
Austrian regulation referred to Art 15a B-VG	✓
Swiss clean air act	<b>*</b>
Crédit d'impôt à la transition énergétique	<b>✓</b>

Evaluation of emission data and efficiency Lignite briquettes	
Norm : Inset appliances (with closed firedoor)	Evaluation
D - 1.BlmSchV	



No symbol means that there are no requirements.

No measuring values are available for this fuel, operation with this fuel is not permitted

Here you will find further information

No information/unknown