

## Appliances properties: Buderus, Bosch Thermotechnik GmbH - HWS 216

Master data

Date of entry Jul 24, 2014

Manufacturer Buderus, Bosch Thermotechnik GmbH

Model HWS 216

Nominal heat output [kW] 8

Continuous burning appliance

Type test standard DIN EN 13229

Year of testing 2014

Test laboratory DBI-Gastechnisches Institut gGmbH Freiberg

Number of test laboratory 12

Number of test report DBI F 13/12/0254

Flue gas values

	Wood
Flue gas mass flow [g/s]	7.34
Flue gas mass flow [g/s]	215
Necessary flue draught [Pa]	15

Further important characteristics of the appliance

Suitability for installation to a shared flue 1)

Connectivity to the central heating system





On behalf of the manufacturer, the HKI Industrieverband e.V. hereby confirms compliance with the respective requirements\* in accordance with 1.BImSchV. The type test report of the fireplace has been submitted to the HKI Industrieverband e.V.

General technical approval for room sealed operation

<sup>1)</sup> For unsealed operation it is possible to install the appliances to a shared flue system (please see installation manual).

<sup>\*</sup> A green check mark with a "1" indicates that the requirements of the 1st BImSchV are fulfilled, a green check mark with a "2" indicates that the 2nd level of the 1st BImSchV is fulfilled. A yellow check mark shows that the transitional regulation of the 1st BImSchV is fulfilled and a red line means that the 1st BImSchV is not fulfilled.

rm : Inset appliance with flat-layer firing	Evaluation
1.BlmSchV	Stufe 2
ustrian regulation referred to Art 15a B-VG	✓
Swiss clean air act	✓
Crédit d'impôt à la transition énergétique	•

Evaluation of emission data and efficiency Lignite briquettes	
Norm : Inset appliance with flat-layer firing	Evaluation
D - 1.BlmSchV	



No symbol means that there are no requirements.

No measuring values are available for this fuel, operation with this fuel is not permitted

Here you will find further information

No information/unknown