

## Appliances properties: Bullerjan GmbH - Bullerjan dot

| Master data                                |                   |
|--|-------------------|
| Date of entry                              | Mar 27, 2014      |
| Manufacturer                               | Bullerjan GmbH    |
| Model                                      | Bullerjan dot     |
| Nominal heat output [kW]                   | 6                 |
| Declared nominal space heating output [kW] | 6                 |
| Continuous burning appliance               | _                 |
| Type test standard                         | DIN EN 13240      |
| Year of testing                            | 2013              |
| Test laboratory                            | RWE Rheinbraun AG |
| Number of test laboratory                  | 4.1               |
| Number of test report                      | FSPS-Wa 2235-EN   |
|  |                   |

| Flue | aas | values |  |
|------|-----|--------|--|
|      |     |        |  |

|                             | Wood |
|-----------------------------|------|
| Flue gas mass flow [g/s]    | 7.5  |
| Flue gas mass flow [g/s]    | 230  |
| Necessary flue draught [Pa] | 12   |

Further important characteristics of the appliance

Suitability for installation to a shared flue 1)



Connectivity to the central heating system

## General technical approval for room sealed operation

On behalf of the manufacturer, the HKI Industrieverband e.V. hereby confirms compliance with the respective requirements\* in accordance with 1.BImSchV. The type test report of the fireplace has been submitted to the HKI Industrieverband e.V.

<sup>&</sup>lt;sup>1)</sup> For unsealed operation it is possible to install the appliances to a shared flue system (please see installation manual).

<sup>\*</sup> A green check mark with a "1" indicates that the requirements of the 1st BImSchV are fulfilled, a green check mark with a "2" indicates that the 2nd level of the 1st BImSchV is fulfilled. A yellow check mark shows that the transitional regulation of the 1st BImSchV is fulfilled and a red line means that the 1st BImSchV is not fulfilled.

## Evaluation of emission data and efficiency Wood

| Norm DIN EN 13240 (Intermittent burning): Roomheater with flat-layer firing | Evaluation |
|---|------------|
| D - 1.BImSchV   | Stufe 2    |
| A - Austrian regulation referred to Art 15a B-VG                            | ✓          |
| CH - Swiss clean air act  | ✓          |
| K - Danish regulation for air pollution from wood burners                   | ✓          |
| - Crédit d'impôt à la transition énergétique                                | 7.4        |

## Evaluation of emission data and efficiency Lignite briquettes

| Norm DIN EN 13240 (Intermittent burning): Roomheater with flat-layer firing | Evaluation |
|---|------------|
| ) - 1.BlmSchV   | Stufe 2    |
| A - Austrian regulation referred to Art 15a B-VG                            | <b>4</b>   |
| CH - Swiss clean air act  | ✓          |
| DK - Danish regulation for air pollution from wood burners                  | •          |



No symbol means that there are no requirements.

No measuring values are available for this fuel, operation with this fuel is not permitted

Here you will find further information

No information/unknown