

## Appliances properties: BRUNNER - HF 5e

tate of entry  anufacturer  BRUNNER  HF 5e  ordinal heat output [kW]  7  ontinuous burning appliance  pe test standard  ar of testing  2001  st laboratory  n.b.  umber of test laboratory  30  umber of test report  Divides as mass flow [g/s]  ue gas mass flow [g/s]  100  ue gas mass flow [g/s]  110  ue gas mass flow [g/s]  120  131  where important characteristics of the appliance  urther important characteristics of the appliance  under the contral heating system  and control in the contral heating system  anufactivity to the central heating system		
anufacturer odel HF 5e  minal heat output [kW] 7  polaried nominal space heating output [kW] 7  minimuous burning appliance pe test standard pe test standard DIN 18892 are of testing DIN 1892 are of testing DIN 18892 are	Master data	
bodel  bodinal heat output [kW]  borninal heat output [kW]  continuous burning appliance	Date of entry	Oct 22, 2012
minal heat output [kW] 7 polared nominal space heating nominal spa	Manufacturer	BRUNNER
reclared nominal space heating output [kW]  rominuous burning appliance  pe test standard  pe test sta	Model	HF 5e
pe test standard DIN 18892 per	Nominal heat output [kW]	7
pe test standard 2001 art of testing 2001 st laboratory n.b. umber of test laboratory 30 umber of test report 1001  The gas values  Wood use gas mass flow [g/s] 10 use gas mass flow [g/s] 170 use ga	Declared nominal space heating output [kW]	7
ar of testing st laboratory n.b. amber of test laboratory 30 amber of test report 1001  Idue gas values  Wood use gas mass flow [g/s] use gas mass flow [g/s] 10 accessary flue draught [Pa]  urther important characteristics of the appliance  uitability for installation to a shared flue <sup>1)</sup> connectivity to the central heating system	Continuous burning appliance	_
st laboratory n.b. umber of test laboratory 30 umber of test report 1001  lue gas values  Wood use gas mass flow [g/s] 10 use gas mass flow [g/s] 170 use gas mass flow [g	Type test standard	DIN 18892
umber of test laboratory  umber of test report  1001  Idue gas values  Wood  use gas mass flow [g/s]  urther important characteristics of the appliance  urther important characteristics of the appliance  untitability for installation to a shared flue 1)  onnectivity to the central heating system	Year of testing	2001
Integration of test report  In	Test laboratory	n.b.
Itue gas values  Wood  use gas mass flow [g/s] 10  use gas mass flow [g/s] 170  cessary flue draught [Pa] 13  urther important characteristics of the appliance  uitability for installation to a shared flue 1)  princctivity to the central heating system	Number of test laboratory	30
Wood use gas mass flow [g/s] 170 use gas mass flow [g/	Number of test report	1001
ue gas mass flow [g/s] 170 ue gas mass flow [g/s] 170 ecessary flue draught [Pa] 13  urther important characteristics of the appliance  uitability for installation to a shared flue 1) ennectivity to the central heating system	Flue gas values	
ue gas mass flow [g/s] secessary flue draught [Pa]  urther important characteristics of the appliance  uitability for installation to a shared flue 1)  onnectivity to the central heating system		
urther important characteristics of the appliance  uitability for installation to a shared flue <sup>1)</sup> onnectivity to the central heating system		
urther important characteristics of the appliance  uitability for installation to a shared flue <sup>1)</sup> connectivity to the central heating system		
uitability for installation to a shared flue <sup>1)</sup> connectivity to the central heating system	Necessary flue draught [Pa]	13
uitability for installation to a shared flue <sup>1)</sup> connectivity to the central heating system		
onnectivity to the central heating system	Further important characteristics of the appliance	
onnectivity to the central heating system	Suitability for installation to a shared fluo <sup>1</sup> )	_
	outdomity for instandation to a shared fide	_
eneral technical approval for room sealed operation	Connectivity to the central heating system	_
	General technical approval for room sealed operation	_

<sup>1)</sup> For unsealed operation it is possible to install the appliances to a shared flue system (please see installation manual).

On behalf of the manufacturer, the HKI Industrieverband e.V. hereby confirms compliance with the respective requirements\* in accordance with 1.BImSchV. The type test report of the fireplace has been submitted to the HKI Industrieverband e.V.

<sup>\*</sup> A green check mark with a "1" indicates that the requirements of the 1st BImSchV are fulfilled, a green check mark with a "2" indicates that the 2nd level of the 1st BImSchV is fulfilled. A yellow check mark shows that the transitional regulation of the 1st BImSchV is fulfilled and a red line means that the 1st BImSchV is not fulfilled.

## Norm: Inset appliances (with closed firedoor) D - 1.BImSchV F - Crédit d'impôt à la transition énergétique

## Evaluation of emission data and efficiency Lignite briquettes

Norm : Inset appliances (with closed firedoor) Evaluation

D - 1.BImSchV

According to the transitional rule §26 the appliance can be used until 31.12.2024



No symbol means that there are no requirements.

No measuring values are available for this fuel, operation with this fuel is not permitted

Here you will find further information

No information/unknown