

Appliances properties: BRUNNER - HF 15

antifacturer BRUNNER odel HF 15 ominal heat output [kW] 14 ontinuous burning appliance		
anufacturer odel HF 15 ominal heat output [kW] 14 ordinal heat output [kW] 15 ordinal heat output [kW] 16 ordinal heat output [kW] 17 ordinal space heating output [kW] 18892 ordinal standard DIN 18892 ordinal standard Ordinal standa	Master data	
odel ominal heat output [kW] perlared nominal space heating output [kW] perlared standard per test standard per test standard per test standard per of testing per test standard per test sta	Date of entry	Oct 22, 2012
cominal heat output [kW] 14 colared nominal space heating output [kW] 14 continuous burning appliance	Manufacturer	BRUNNER
actared nominal space heating output [kW] ontinuous burning appliance pee test standard DIN 18892 2002 stalaboratory n.b. umber of test laboratory 30 umber of test report Divide gas values Tue gas wass flow [g/s] ue gas mass flow [g/s] 16 ue gas mass flow installation to a shared flue 1) unther important characteristics of the appliance uitability for installation to a shared flue 1) onnectivity to the central heating system	Model	HF 15
pre test standard DIN 18892 par of testing 2002 part laboratory n.b. pumber of test laboratory 30 pumber of test report 2002 pumber of test report 2002 pumber of test report 160 pumber of test report	Nominal heat output [kW]	14
pe test standard 2002 par of testing 2002 past laboratory 2002 part laboratory 30 pumber of test laboratory 2002 pumber of test report 2002 pumber of test laboratory 30 pumber of te	Declared nominal space heating output [kW]	14
set laboratory n.b. sumber of test laboratory 30 sumber of test report 2002 stillue gas values Sumber of test report 2002 Sumber of test laboratory 30 Sumber of te	Continuous burning appliance	_
In the set laboratory and sumber of test laboratory and sumber of test report and set report and	Type test standard	DIN 18892
umber of test laboratory 2002 Flue gas values Wood ue gas mass flow [g/s] 16 ue gas mass flow [g/s] 160 ecessary flue draught [Pa] 14 Further important characteristics of the appliance Litability for installation to a shared flue 1) connectivity to the central heating system 2002	Year of testing	2002
titue gas values Wood ue gas mass flow [g/s] 16 ue gas mass flow [g/s] 160 ecessary flue draught [Pa] 14 further important characteristics of the appliance uitability for installation to a shared flue ¹⁾ connectivity to the central heating system	Test laboratory	n.b.
idue gas values Wood ue gas mass flow [g/s] 16 ue gas mass flow [g/s] 160 ecessary flue draught [Pa] 14 idurther important characteristics of the appliance uitability for installation to a shared flue 1) connectivity to the central heating system	Number of test laboratory	30
we gas mass flow [g/s] ue gas mass flow [g/s] ue cessary flue draught [Pa] further important characteristics of the appliance uitability for installation to a shared flue ¹⁾ onnectivity to the central heating system	Number of test report	2002
ue gas mass flow [g/s] ue gas mass flow [g/s] ecessary flue draught [Pa] further important characteristics of the appliance uitability for installation to a shared flue 1) onnectivity to the central heating system	Flue gas values	
ue gas mass flow [g/s] ecessary flue draught [Pa] further important characteristics of the appliance uitability for installation to a shared flue 1) onnectivity to the central heating system		
Further important characteristics of the appliance Luitability for installation to a shared flue ¹⁾ Connectivity to the central heating system		
Further important characteristics of the appliance uitability for installation to a shared flue ¹⁾ connectivity to the central heating system		
uitability for installation to a shared flue ¹⁾ connectivity to the central heating system	Necessary flue draught [Pa]	14
uitability for installation to a shared flue ¹⁾ connectivity to the central heating system		
onnectivity to the central heating system	Further important characteristics of the appliance	
onnectivity to the central heating system	Suitability for installation to a abard flus 1)	
	Suitability for instandation to a shared fide /	_
eneral technical approval for room sealed operation	Connectivity to the central heating system	_
	General technical approval for room sealed operation	_

¹⁾ For unsealed operation it is possible to install the appliances to a shared flue system (please see installation manual).

On behalf of the manufacturer, the HKI Industrieverband e.V. hereby confirms compliance with the respective requirements* in accordance with 1.BImSchV. The type test report of the fireplace has been submitted to the HKI Industrieverband e.V.

^{*} A green check mark with a "1" indicates that the requirements of the 1st BImSchV are fulfilled, a green check mark with a "2" indicates that the 2nd level of the 1st BImSchV is fulfilled. A yellow check mark shows that the transitional regulation of the 1st BImSchV is fulfilled and a red line means that the 1st BImSchV is not fulfilled.

Norm: Inset appliances (with closed firedoor) D - 1.BImSchV F - Crédit d'impôt à la transition énergétique

Evaluation of emission data and efficiency Lignite briquettes

Norm : Inset appliances (with closed firedoor) Evaluation

D - 1.BImSchV

According to the transitional rule §26 the appliance can be used until 31.12.2024



No symbol means that there are no requirements.

No measuring values are available for this fuel, operation with this fuel is not permitted

Here you will find further information

No information/unknown