

## Appliances properties: Wodtke GmbH - Kompakt KE 01.6

Master data

Date of entryJan 14, 2009ManufacturerWodtke GmbH

Model Kompakt KE 01.6

Nominal heat output [kW]

Continuous burning appliance

Type test standard DIN 18892

Year of testing 1986

Test laboratory Wodtke GmbH DIN Certco Werksprüfstelle

Number of test laboratory 16
Number of test report 85/19



Flue gas values

	Wood
Flue gas mass flow [g/s]	6
Flue gas mass flow [g/s]	350
Necessary flue draught [Pa]	16

Further important characteristics of the appliance

Suitability for installation to a shared flue 1)



Connectivity to the central heating system

## General technical approval for room sealed operation

On behalf of the manufacturer, the HKI Industrieverband e.V. hereby confirms compliance with the respective requirements\* in accordance with 1.BImSchV. The type test report of the fireplace has been submitted to the HKI Industrieverband e.V.

<sup>1)</sup> For unsealed operation it is possible to install the appliances to a shared flue system (please see installation manual).

<sup>\*</sup>A green check mark with a "1" indicates that the requirements of the 1st BImSchV are fulfilled, a green check mark with a "2" indicates that the 2nd level of the 1st BImSchV is fulfilled. A yellow check mark shows that the transitional regulation of the 1st BImSchV is fulfilled and a red line means that the 1st BImSchV is not fulfilled.

## Norm: Inset appliances with feeder firing D - 1.BImSchV F - Crédit d'impôt à la transition énergétique

## Evaluation of emission data and efficiency Lignite briquettes

Evaluation of emission data and efficiency Wood

Norm : Inset appliances with feeder firing	Evaluation
D - 1.BlmSchV	_



No symbol means that there are no requirements.

No measuring values are available for this fuel, operation with this fuel is not permitted

Here you will find further information

No information/unknown