

Appliances properties: Spartherm Feuerungstechnik GmbH - Mini R1V (Bauart A; ab 2000)

te of entry Interest of entry Interest of entry Nov 26, 2011 Spartherm Feuerungstechnik GmbH Mini R1V (Bauart A; ab 2000) Intinuous burning appliance Intinuous burning appliance Interest standard DIN 18895 Interest at aboratory DMT Feuerstätten Prüfstelle Interest laboratory Interest laboratory Interest laboratory Interest laboratory Interest laboratory Interest report Wood Interest report Wood Interest report Interest rep			
anufacturer spartherm Feuerungstechnik GmbH Mini R1V (Bauart A; ab 2000) 6 Intinuous burning appliance pe test standard ar of testing 2000 St laboratory DMT Feuerstätten Prüfstelle Jumber of test laboratory 20 RO-95 00 76 Wood Jue gas wass flow [g/s] Jue gas mass flow [g/s] Jue	Master data		
anufacturer spartherm Feuerungstechnik GmbH Mini R1V (Bauart A; ab 2000) 6 ontinuous burning appliance pe test standard ar of testing 2000 St laboratory DMT Feuerstätten Prüfstelle umber of test laboratory 20 RO-95 00 76 Wood use gas mass flow [g/s] seessary flue draught [Pa] where important characteristics of the appliance urther important characteristics of the appliance stability for installation to a shared flue 1) onnectivity to the central heating system	Date of entry	Nov 26, 2011	
ominal heat output [kW] 6 ontinuous burning appliance — pe test standard DIN 18895 par of testing 2000 pMT Feuerstätten Prüfstelle purber of test laboratory 20 purber of test report RO-95 00 76 The gas mass flow [g/s] 5.4 pur gas mass flow [g/s] 5.4 pur gas mass flow [g/s] 14 pur gas mass flow [g/s] 15 pur gas mass	Manufacturer	Spartherm Feuerungstechnik GmbH	
pe test standard DIN 18895 per	Model	Mini R1V (Bauart A; ab 2000)	
pe test standard DIN 18895 par of testing 2000 st laboratory DMT Feuerstätten Prüfstelle pumber of test laboratory 20 pumber of test report RO-95 00 76 Tue gas values Wood use gas mass flow [g/s] 5.4 use gas mass flow [g/s] 270 pressary flue draught [Pa] 14 Purther important characteristics of the appliance witability for installation to a shared flue ¹⁾ pumber of test report RO-95 00 76	Nominal heat output [kW]	6	
ar of testing st laboratory DMT Feuerstätten Prüfsteile Imber of test laboratory DMT Feuerstätten Prüfsteile Imber of test laboratory RO-95 00 76 Ilue gas values Wood Use gas mass flow [g/s] Use g	Continuous burning appliance	_	
st laboratory umber of test laboratory 20 RO-95 00 76 Wood use gas mass flow [g/s] use gas mass flow [g/s] seessary flue draught [Pa] urther important characteristics of the appliance uitability for installation to a shared flue ¹⁾ connectivity to the central heating system	Type test standard	DIN 18895	
unber of test laboratory unber of test report RO-95 00 76 RO-95 00 76 RO-95 00 76 Wood use gas mass flow [g/s] use gas flow [g/s] use gas flow [g/s] use gas flow [g/s] use gas flow [g/s] use ga	Year of testing	2000	
Itue gas values Wood	Test laboratory	DMT Feuerstätten Prüfstelle	
Itue gas values Wood ue gas mass flow [g/s] 5.4 ue gas mass flow [g/s] 270 ecessary flue draught [Pa] 14 urther important characteristics of the appliance uitability for installation to a shared flue 1) ennectivity to the central heating system	Number of test laboratory	20	
wood use gas mass flow [g/s] u	Number of test report	RO-95 00 76	
wood use gas mass flow [g/s] u			
ue gas mass flow [g/s] 270 ue gas mass flow [g/s] 270 ue cessary flue draught [Pa] 14 urther important characteristics of the appliance uitability for installation to a shared flue 1) ennectivity to the central heating system 5.4	Flue gas values		
ue gas mass flow [g/s] 270 ecessary flue draught [Pa] 14 urther important characteristics of the appliance uitability for installation to a shared flue ¹⁾ onnectivity to the central heating system			Wood
urther important characteristics of the appliance uitability for installation to a shared flue ¹⁾ onnectivity to the central heating system	Flue gas mass flow [g/s]		5.4
urther important characteristics of the appliance uitability for installation to a shared flue ¹⁾ onnectivity to the central heating system	Flue gas mass flow [g/s]		270
uitability for installation to a shared flue ¹⁾ connectivity to the central heating system	Necessary flue draught [Pa]		14
uitability for installation to a shared flue ¹⁾ connectivity to the central heating system			
onnectivity to the central heating system	Further important characteristics of the appliance		
onnectivity to the central heating system			
	Suitability for installation to a shared flue ¹⁾		_
eneral technical approval for room sealed operation	Connectivity to the central heating system		_
	General technical approval for room sealed operation		_

¹⁾ For unsealed operation it is possible to install the appliances to a shared flue system (please see installation manual).

On behalf of the manufacturer, the HKI Industrieverband e.V. hereby confirms compliance with the respective requirements* in accordance with 1.BImSchV. The type test report of the fireplace has been submitted to the HKI Industrieverband e.V.

^{*} A green check mark with a "1" indicates that the requirements of the 1st BImSchV are fulfilled, a green check mark with a "2" indicates that the 2nd level of the 1st BImSchV is fulfilled. A yellow check mark shows that the transitional regulation of the 1st BImSchV is fulfilled and a red line means that the 1st BImSchV is not fulfilled.

Norm: Inset appliances (with closed firedoor) D - 1.BImSchV A - Austrian regulation referred to Art 15a B-VG CH - Swiss clean air act F - Crédit d'impôt à la transition énergétique

Evaluation of emission data and efficiency Lignite briquettes

Norm: Inset appliances (with closed firedoor)

Evaluation

D - 1.BImSchV

According to the transitional rule §26 the appliance can be used until 31.12.2024



No symbol means that there are no requirements.

No measuring values are available for this fuel, operation with this fuel is not permitted

Here you will find further information

No information/unknown