

Appliances properties: Dovre N.V. - 550GM

Master data

Date of entry Apr 2, 2015 Dovre N.V. Manufacturer Model 550GM Nominal heat output [kW] 8 Declared nominal space heating output [kW] Continuous burning appliance **DIN EN 13240** Type test standard Year of testing 2011 LABORATORY K.V.B.G. - A.R.G.B. **Test laboratory**

Number of test laboratory17Number of test reportH0084



Flue gas values

	Wood
Flue gas mass flow [g/s]	9.2
Flue gas mass flow [g/s]	290
Necessary flue draught [Pa]	12

Further important characteristics of the appliance

Suitability for installation to a shared flue 1)

Connectivity to the central heating system

General technical approval for room sealed operation

On behalf of the manufacturer, the HKI Industrieverband e.V. hereby confirms compliance with the respective requirements* in accordance with 1.BImSchV. The type test report of the fireplace has been submitted to the HKI Industrieverband e.V.

* A green check mark with a "1" indicates that the requirements of the 1st BImSchV are fulfilled, a green check mark with a "2" indicates that the 2nd level of the 1st BImSchV is fulfilled. A yellow check mark shows that the transitional regulation of the 1st BImSchV is fulfilled and a red line means that the 1st BImSchV is not fulfilled.

¹⁾ For unsealed operation it is possible to install the appliances to a shared flue system (please see installation manual).

Norm DIN EN 13240 (Intermittent burning): Roomheater with flat-layer firing D - 1.BImSchV A - Austrian regulation referred to Art 15a B-VG

CH - Swiss clean air act

D - 1.BImSchV

F - Crédit d'impôt à la transition énergétique

Evaluation of emission data and efficiency Lignite briquettes	
Norm DIN EN 13240 (Intermittent burning): Roomheater with flat-layer firing	Evaluation



No symbol means that there are no requirements.

No measuring values are available for this fuel, operation with this fuel is not permitted

Here you will find further information

No information/unknown