

Appliances properties: BRUNNER - HF 10e

Master data	
Date of entry	Oct 22, 2012
Manufacturer	BRUNNER
Model Nominal heat output [kW]	HF 10e 11
Continuous burning appliance	_
Type test standard	DIN 18892
Year of testing	2002
Test laboratory	n.b.
Number of test laboratory	30
Number of test report	2001
Flue gas values	
Flue gas mass flow [g/s]	Wood 14
Flue gas mass flow [g/s]	170
Necessary flue draught [Pa]	14
	··
Further important characteristics of the appliance	
Suitability for installation to a shared flue ¹⁾	_
Connectivity to the central heating system	_
General technical approval for room sealed operation	_

¹⁾ For unsealed operation it is possible to install the appliances to a shared flue system (please see installation manual).

On behalf of the manufacturer, the HKI Industrieverband e.V. hereby confirms compliance with the respective requirements* in accordance with 1.BImSchV. The type test report of the fireplace has been submitted to the HKI Industrieverband e.V.

^{*} A green check mark with a "1" indicates that the requirements of the 1st BImSchV are fulfilled, a green check mark with a "2" indicates that the 2nd level of the 1st BImSchV is fulfilled. A yellow check mark shows that the transitional regulation of the 1st BImSchV is fulfilled and a red line means that the 1st BImSchV is not fulfilled.

Norm: Inset appliances (with closed firedoor) D - 1.BImSchV F - Crédit d'impôt à la transition énergétique

Evaluation of emission data and efficiency Lignite briquettes

Norm : Inset appliances (with closed firedoor) Evaluation

D - 1.BImSchV

According to the transitional rule §26 the appliance can be used until 31.12.2024



No symbol means that there are no requirements.

No measuring values are available for this fuel, operation with this fuel is not permitted

Here you will find further information

No information/unknown