

Appliances properties: Buderus, Bosch Thermotechnik GmbH - 171.1/176.1

Nominal heat output [kW] 8.7 Continuous burning appliance — Type test standard DIN 18892 Type test standard 1975 Replacement heating insert	Master data	
Manufacturer Buderus, Bosch Thermotechnik GmbH Model 171.1/176.1 Nominal heat output [W] 8.7 Continuous burning appliance — Pype test standard DIN 18892 Replacement heating insert — HLS116/216, HWS216, H107H — Further important characteristics of the appliance — Buthating insert — HLS116/216, HWS216, H107H — Further important characteristics of the appliance — Boneral technical approval for room sequence instantiation namual). — Connectivity to the central heating system — General technical approval for room sequence instantiation manual). — Profuse and digeneration at the requirements of the latelinder with the respective requirements in accordance with 18.BinSchV. The type test report of the filedeet has Anard A		
Nodel 171.1176.1 Nominal heat output [KW] 8.7 Continuous burning appliance — Type test standard DIN 18892 Replacement heating insert 1975 HLS116/216, HWS216, H107H — Further important characteristics of the appliance — Suitability for installation to a shared flue ¹) — Connectivity to the central heating system — Operational the appliance to the system (bees see installation manual). — Debut of the manuface, the KV (manuse shared flue system (bees see installation manual). — Prove means the test installation to a shared flue system (bees see installation manual). — Prove means the test installation of the appliance to a shared flue system (bees see installation manual). — Prove means the the installation to a shared flue system (bees see installation manual). — Prove means the installation of the system of the system (bees see installation manual). — Prove means the the requerement of the system	•	
Nominal heat output [kW] 2.7 Continuous burning appliance DIN 18892 Year of testing 1975 Replacement heating insert -LIS116/216, HWS216, H107H Further important characteristics of the appliance Suitability for installation to a shared flue ¹) -Connectivity to the central heating system General technical approval for room sealed operation 		
Continuous burning appliance — Type test standard DIN 18892 Replacement heating insert 1975 Replacement heating insert — 4LS116/216, HWS216, H107H — Further important characteristics of the appliance — Suitability for installation to a shared flue ¹⁾ — Connectivity to the central heating system — General technical approval for room sealed operation — "Por unsealed operation it is possible to install the appliance to the fireplace has existentiate to the installation to a shared flue system (please see installation manual). — Do behalf of the manufacture; Jie HKI Industreventand e V. hereby confirms compliance with the respective requirements in accordance with 1 BINSchV. The type test report of the fireplace has existentiate to the stall BinSchV is buffled. A velow other mark with a _1" indicates that the requirements of the fireplace has existentiate to the stall BinSchV is buffled. A velow other mark with a _1" indicates that the requirements of the fireplace has existentiate to the stall BinSchV is buffled. A velow other with a has an of fullee of the fireplace has existentiated bear existentiate and a red line means that the fire binSchV is not fullee.	Model	
Type test standard DIN 18892 Year of testing 1975 Replacement heating insert HLS116/216, HWS216, H107H Further important characteristics of the appliance Further important characteristics of the appliance Connectivity for installation to a shared flue ¹) General technical approval for room sealed operation Pure unsealed operation it is possible to install the appliances to a shared flue system (please see installation manual). On behalt the financiacular physical data and efficiency Wood Evaluation of emission data and efficiency Wood Pure lines appliance with flat-layer firing Evaluation	Nominal heat output [kW]	8.7
Year of testing 1975 Replacement heating insert	Continuous burning appliance	—
Replacement heating insert HLS116/216, HWS216, H107H Further important characteristics of the appliance Suitability for installation to a shared flue ¹) Connectivity to the central heating system General technical approval for room sealed operation Piror unsealed operation it is possible to install the appliances to a shared flue system (please see installation manual). On behalf of the manufacture, the HKI industrieventual of the 1st BimSchV are fulfiled, a green check mark with a 1.2 indicates that the 2.2 indicates that the 2	Type test standard	DIN 18892
HLS116/216, HWS216, H107H Further important characteristics of the appliance Suitability for installation to a shared flue ¹⁾ Connectivity to the central heating system General technical approval for noom sealed operation ¹⁾ For unsealed operation it is possible to install the appliances to a shared flue system (please see installation manual). On bland of the mundcuture: the HU Industrieventand e.V. hereby confirms compliance with the respective requirements' in accordance with 1.BImSchV. The type test report of the fireplace has been submitted to the HKI Industrieventand e.V. A green check mark with a _1' indicates that the requirements of the 1st BImSchV are fulfilled, a green check mark with a _2' indicates that the 2nd level of the 1st BImSchV is fulfilled. A yellow chem mark shows that the transitional regulation of the 1st BImSchV is fulfilled. A yellow chem mark with a _2' indicates that the fast BImSchV is fulfilled. A yellow chem mark with a _1' indicates that the requirements of the 1st BImSchV is fulfilled. A yellow chem mark with a _2' indicates that the 2nd level of the 1st BImSchV is fulfilled. A yellow chem mark with a _2' indicates that the fast BImSchV is fulfilled. A yellow chem mark with a _2' indicates that the 2nd level of the 1st BImSchV is fulfilled. A yellow chem mark with a _2' indicates that the 2nd level of the 1st BImSchV is fulfilled. A yellow chem mark is the transitional regulation of the 1st BImSchV is fulfilled. Evaluation of emission data and efficiency Wood I Norm : Inset appliance with flat-layer firing Evaluation Conding to the transitional rule §26 the appliance can be used un	Year of testing	1975
Further important characteristics of the appliance Suitability for installation to a shared flue ¹) Connectivity to the central heating system General technical approval for room sealed operation ¹⁰ For unsealed operation it is possible to install the appliances to a shared flue system (please see installation manual). On behalf of the manufacturer, the HKI Industrieverband e.V. hereby confirms compliance with the respective requirements in accordance with 1.BImSchV. The type test report of the firsplace has earner with a .1 ² indicates that the requirements of the 1st BImSchV are fulfilled, a green check mark with a .2 ² indicates that the 2nd level of the 1st BImSchV is fulfilled. A yellow chemark shows that the transitional regulation of the 1st BImSchV is fulfilled and a red line means that the 1st BImSchV is not fulfilled. Evaluation of emission data and efficiency Wood Interplace with flat-layer firing Cording to the transitional rule §26 the appliance can be used until 31.12.2017	Replacement heating insert	
Suitability for installation to a shared flue ¹⁾	HLS116/216, HWS216, H107H	
General technical approval for room sealed operation Image: Construction of the system of the appliances to a shared flue system (please see installation manual). On behalf of the manufacturer, the HKI Industrieverband e.V. hereby confirms compliance with the respective requirements' in accordance with 1.BImSchV. The type test report of the fireplace has been submitted to the HKI Industrieverband e.V. 'A green check mark with a "1" indicates that the requirements of the 1st BImSchV are fulfilled, a green check mark with a "2" indicates that the 2nd level of the 1st BImSchV is fulfilled. A yellow chere mark shows that the transitional regulation of the 1st BImSchV is fulfilled and a red line means that the 1st BImSchV is not fulfilled. Evaluation of emission data and efficiency Wood Evaluation Or 1.BImSchV Control flat-layer firing Control flat SchV According to the transitional rule §26 the appliance can be used until 31.12.2017	Further important characteristics of the appliance Suitability for installation to a shared flue ¹⁾	
¹⁾ For unsealed operation it is possible to install the appliances to a shared flue system (please see installation manual). On behalf of the manufacturer, the HKI Industrieverband e.V. hereby confirms compliance with the respective requirements* in accordance with 1.BImSchV. The type test report of the fireplace has been submitted to the HKI Industrieverband e.V. A green check mark with a _1* indicates that the requirements of the 1st BImSchV are fulfilled, a green check mark with a _2* indicates that the 2nd level of the 1st BImSchV is fulfilled. A yellow check mark shows that the transitional regulation of the 1st BImSchV is fulfilled and a red line means that the 1st BImSchV is not fulfilled. Evaluation of emission data and efficiency Wood Evaluation of emission data and efficiency Wood D - 1.BImSchV C - 1.BImSchV Evaluation the transitional rule §26 the appliance can be used until 31.12.2017	Connectivity to the central heating system	
Do behalf of the manufacturer, the HKI Industrieverband e.V. hereby confirms compliance with the respective requirements* in accordance with 1.BImSchV. The type test report of the fireplace has been submitted to the HKI Industrieverband e.V. A green check mark with a _1* indicates that the requirements of the 1st BImSchV are fulfilled, a green check mark with a _2* indicates that the 2nd level of the 1st BImSchV is fulfilled. A yellow check mark shows that the transitional regulation of the 1st BImSchV is fulfilled and a red line means that the 1st BImSchV is not fulfilled. Evaluation of emission data and efficiency Wood Norm : Inset appliance with flat-layer firing D - 1.BImSchV According to the transitional rule §26 the appliance can be used until 31.12.2017	General technical approval for room sealed oper	ration
been submitted to the HKI Industrieverband e.V. 'A green check mark with a "1" indicates that the requirements of the 1st BImSchV are fulfilled, a green check mark with a "2" indicates that the 2nd level of the 1st BImSchV is fulfilled. A yellow check mark shows that the transitional regulation of the 1st BImSchV is fulfilled and a red line means that the 1st BImSchV is not fulfilled. Evaluation of emission data and efficiency Wood Norm : Inset appliance with flat-layer firing C - 1.BImSchV According to the transitional rule §26 the appliance can be used until 31.12.2017	¹⁾ For unsealed operation it is possible to install the appliances to	o a shared flue system (please see installation manual).
Evaluation of emission data and efficiency Wood Norm : Inset appliance with flat-layer firing Evaluation 0 - 1.BImSchV According to the transitional rule §26 the appliance can be used until 31.12.2017	On behalf of the manufacturer, the HKI Industrieverband e.V. here been submitted to the HKI Industrieverband e.V.	eby confirms compliance with the respective requirements* in accordance with 1.BImSchV. The type test report of the fireplace has
Norm : Inset appliance with flat-layer firing Evaluation D - 1.BImSchV According to the transitional rule §26 the appliance can be used until 31.12.2017		
Norm : Inset appliance with flat-layer firing Evaluation D - 1.BImSchV According to the transitional rule §26 the appliance can be used until 31.12.2017		
Norm : Inset appliance with flat-layer firing Evaluation D - 1.BImSchV According to the transitional rule §26 the appliance can be used until 31.12.2017	Evaluation of emission data and efficiency Wood	
D - 1.BImSchV According to the transitional rule §26 the appliance can be used until 31.12.2017		
According to the transitional rule §26 the appliance can be used until 31.12.2017	Norm : Inset appliance with flat-layer firing	Evaluation
	D - 1.BImSchV	According to the transitional rule §26 the appliance can be used until 31.12.2017
	F - Crédit d'impôt à la transition énergétique	1

Evaluation of emission data and efficiency Lignite briquettes	
Norm : Inset appliance with flat-layer firing	Evaluation
D - 1.BImSchV	According to the transitional rule §26 the appliance can be used until 31.12.2017

Emission evaluation legend

Stufe 2	Compliant with the requirements of the 2nd stage of the 1.BImSchV (only for Germany)
Stufe 1	Compliant with the requirements of the 1st stage of the 1.BImSchV (only for Germany)
2015	Compliant with the requirements of the Austrian Agreement pursuant to Art. 15a B-VG from 2015 (applies only to Austria)
7☆	Compliant with the requirements for the "Crédit d'impôt" promotion in France, the fireplace complies with the classification 7* of the Flamme Verte Label
<mark>6☆</mark>	Compliant with the requirements for the "Crédit d'impôt" promotion in France, the fireplace complies with the classification 6* of the Flamme Verte Label
5☆	Compliant with the requirements for the "Crédit d'impôt" promotion in France, the fireplace complies with the classification 5* of the Flamme Verte Label
☆	Compliant with the requirements of the 1 star stage in Italy.
食食	Compliant with the requirements of the 2 star stage in Italy.
全 京会	Compliant with the requirements of the 3 star stage in Italy.
* 京京京京	Compliant with the requirements of the 4 star stage in Italy.
***	Compliant with the requirements of the 5 star stage in Italy.
	Fulfils the requirements
\checkmark	Complies with requirements of the transition ruling (1.BImSchV)
-	Requirements are not fulfilled
_	No information/unknown
ľ	No measuring values are available for this fuel, operation with this fuel is not permitted
Nosv	mbol means that there are no requirements

No symbol means that there are no requirements. Here you will find further information