

Appliances properties: Rizzoli GmbH - RI90

Master data			
Date of entry	May 11, 2017		
Manufacturer	Rizzoli GmbH		
Model	RI90		
Nominal heat output [kW]	8		
Continuous burning appliance	DIN EN 12815		
Type test standard			
Year of testing	2015 ACTECO SRL		
Test laboratory			
Number of test laboratory	33		
Number of test report	1880-CPR-032-15		
Flue gas values			
		Wood	
Flue gas mass flow [g/s]		8.6	
Flue gas mass flow [g/s]		149.9	
Necessary flue draught [Pa]		6	
Further important characteristics of the appliance			
Suitability for installation to a shared flue ¹⁾		_	
Connectivity to the central heating system		_	

¹⁾ For unsealed operation it is possible to install the appliances to a shared flue system (please see installation manual).

On behalf of the manufacturer, the HKI Industrieverband e.V. hereby confirms compliance with the respective requirements* in accordance with 1.BImSchV. The type test report of the fireplace has been submitted to the HKI Industrieverband e.V.

^{*} A green check mark with a "1" indicates that the requirements of the 1st BImSchV are fulfilled, a green check mark with a "2" indicates that the 2nd level of the 1st BImSchV is fulfilled. A yellow check mark shows that the transitional regulation of the 1st BImSchV is fulfilled and a red line means that the 1st BImSchV is not fulfilled.

Norm : Cookers D - 1.BImSchV A - Austrian regulation referred to Art. 15a B-VG CH - Swiss clean air act

ſ				
Evaluation of	of omiccion	data a	nd officionav I	ignito briguettes

Evaluation of emission data and efficiency Wood

F - Crédit d'impôt à la transition énergétique

Norm : Cookers	Evaluation
D - 1.BImSchV	!

Evaluation of emission data and efficiency Pellets

Norm : Cookers	Evaluation
D - 1.BlmSchV	ļ.



No symbol means that there are no requirements.

No measuring values are available for this fuel, operation with this fuel is not permitted

Here you will find further information

No information/unknown