

Appliances properties: Palazzetti Lelio S. p. A. - ECOMONOBLOCCO 64 O2RING

Master data		
Date of entry	Mar 8, 2013	
Manufacturer	Palazzetti Lelio S. p. A.	
Model	ECOMONOBLOCCO 64 O2RING	
Nominal heat output [kW]	14.5	
Continuous burning appliance	_	
Type test standard	DIN EN 13229	
Year of testing	2012	
Test laboratory	TÜV RHEINLAND INDUSTRIE SERVICE GMBH - TÜV Rheinland Group	
Number of test laboratory	5	
Number of test report	K 705 2012 T1	
Flue gas values		
		Wood
Flue gas mass flow [g/s]		13.3
Flue gas mass flow [g/s]		238.7
Necessary flue draught [Pa]		11
Further important characteristics of the a	ppliance	
Suitability for installation to a shared fl	ue ¹⁾	_
Connectivity to the central heating system		

¹⁾ For unsealed operation it is possible to install the appliances to a shared flue system (please see installation manual).

General technical approval for room sealed operation

On behalf of the manufacturer, the HKI Industrieverband e.V. hereby confirms compliance with the respective requirements* in accordance with 1.BImSchV. The type test report of the fireplace has been submitted to the HKI Industrieverband e.V.

^{*} A green check mark with a "1" indicates that the requirements of the 1st BImSchV are fulfilled, a green check mark with a "2" indicates that the 2nd level of the 1st BImSchV is fulfilled. A yellow check mark shows that the transitional regulation of the 1st BImSchV is fulfilled and a red line means that the 1st BImSchV is not fulfilled.

rm : Inset appliance with flat-layer firing	Evaluation
1.BlmSchV	Stufe 2
ustrian regulation referred to Art 15a B-VG	✓
Swiss clean air act	✓
Crédit d'impôt à la transition énergétique	•

Evaluation of emission data and efficiency Lignite briquettes				
Norm : Inset appliance with flat-layer firing	Evaluation			
D - 1.BlmSchV				



No symbol means that there are no requirements.

No measuring values are available for this fuel, operation with this fuel is not permitted

Here you will find further information

No information/unknown