

Appliances properties: Olsberg GmbH - Olsberg - Quadro mit Topfentaschung - 19/248

Master data

Date of entry Apr 6, 2011

Manufacturer Olsberg GmbH - Olsberg

Model Quadro mit Topfentaschung

Product code 19/248

Nominal heat output [kW]

Continuous burning appliance

Type test standard DIN 18895

Year of testing 1994



Further important characteristics of the appliance

Suitability for installation to a shared flue 1)

Connectivity to the central heating system

General technical approval for room sealed operation

On behalf of the manufacturer, the HKI Industrieverband e.V. hereby confirms compliance with the respective requirements* in accordance with 1.BImSchV. The type test report of the fireplace has been submitted to the HKI Industrieverband e.V.

Evaluation of emission data and efficiency Wood

Norm : Inset appliances (with closed firedoor)

Evaluation

D - 1.BImSchV

According to the transitional rule §26 the appliance can be used until 31.12.2020

Evaluation of emission data and efficiency Lignite briquettes


Norm : Inset appliances (with closed firedoor)

Evaluation

D - 1.BImSchV

¹⁾ For unsealed operation it is possible to install the appliances to a shared flue system (please see installation manual).

^{*}A green check mark with a "1" indicates that the requirements of the 1st BImSchV are fulfilled, a green check mark with a "2" indicates that the 2nd level of the 1st BImSchV is fulfilled. A yellow check mark shows that the transitional regulation of the 1st BImSchV is fulfilled and a red line means that the 1st BImSchV is not fulfilled.



No symbol means that there are no requirements.

No measuring values are available for this fuel, operation with this fuel is not permitted

Here you will find further information