



Appliances properties: Austroflamm GmbH - Herkules

Master data

| | |
|---|--|
| Date of entry | Aug 7, 2014 |
| Manufacturer | Austroflamm GmbH |
| Model | Herkules |
| Nominal heat output [kW] | 10 |
| Declared nominal space heating output [kW] | 10 |
| Continuous burning appliance | — |
| Thermal output | 36,000 |
| Type test standard | DIN EN 13229 |
| Year of testing | 2007 |
| Test laboratory | RRF Rhein-Ruhr-Feuerstättenprüfstelle GmbH |
| Number of test laboratory | 2 |
| Number of test report | RRF - 29 07 1437 |

Flue gas values

| | Wood |
|------------------------------------|------|
| Flue gas mass flow [g/s] | 9.6 |
| Flue gas mass flow [g/s] | 300 |
| Necessary flue draught [Pa] | 12 |

Further important characteristics of the appliance

Suitability for installation to a shared flue¹⁾



Connectivity to the central heating system



General technical approval for room sealed operation



¹⁾ For unsealed operation it is possible to install the appliances to a shared flue system (please see installation manual).


On behalf of the manufacturer, the HKI Industrieverband e.V. hereby confirms compliance with the respective requirements* in accordance with 1.BImSchV. The type test report of the fireplace has been submitted to the HKI Industrieverband e.V.

* A green check mark with a „1“ indicates that the requirements of the 1st BImSchV are fulfilled, a green check mark with a „2“ indicates that the 2nd level of the 1st BImSchV is fulfilled. A yellow check mark shows that the transitional regulation of the 1st BImSchV is fulfilled and a red line means that the 1st BImSchV is not fulfilled.

Evaluation of emission data and efficiency Wood

| Norm : Inset appliances (with closed firedoor) | Evaluation |
|--|---|
| D - 1.BImSchV |  Grandfathering |
| A - Austrian regulation referred to Art 15a B-VG |  |
| CH - Swiss clean air act |  |
| F - Crédit d'impôt à la transition énergétique |  |

Evaluation of emission data and efficiency Lignite briquettes

| Norm : Inset appliances (with closed firedoor) | Evaluation |
|--|--|
| D - 1.BImSchV |  According to the transitional rule §26 the appliance can be used until 31.12.2024 |

- 
Stufe 2 Compliant with the requirements of the 2nd stage of the 1.BImSchV (only for Germany)
- 
Stufe 1 Compliant with the requirements of the 1st stage of the 1.BImSchV (only for Germany)
- 
2015 Compliant with the requirements of the Austrian Agreement pursuant to Art. 15a B-VG from 2015 (applies only to Austria)
- 
7★ Compliant with the requirements for the „Crédit d'impôt“ promotion in France, the fireplace complies with the classification 7* of the Flamme Verte Label
- 
6★ Compliant with the requirements for the „Crédit d'impôt“ promotion in France, the fireplace complies with the classification 6* of the Flamme Verte Label
- 
5★ Compliant with the requirements for the „Crédit d'impôt“ promotion in France, the fireplace complies with the classification 5* of the Flamme Verte Label
- 
★ Compliant with the requirements of the 1 star stage in Italy.
- 
★★ Compliant with the requirements of the 2 star stage in Italy.
- 
★★★ Compliant with the requirements of the 3 star stage in Italy.
- 
★★★★ Compliant with the requirements of the 4 star stage in Italy.
- 
★★★★★ Compliant with the requirements of the 5 star stage in Italy.
-  Fulfils the requirements
-  Complies with requirements of the transition ruling (1.BImSchV)
-  Requirements are not fulfilled
-  No information/unknown
-  No measuring values are available for this fuel, operation with this fuel is not permitted

No symbol means that there are no requirements.

Here you will find further information