

Appliances properties: Palazzetti Lelio S. p. A. - ECOMONOBLOCCO 86 O2RING

Master data Date of entry Mar 8, 2013 Manufacturer Palazzetti Lelio S. p. A. Model ECOMONOBLOCCO 86 O2RING Nominal heat output [kW] 26.8 Continuous burning appliance Type test standard **DIN EN 13229** 2012 Year of testing **Test laboratory** TÜV RHEINLAND INDUSTRIE SERVICE GMBH - TÜV Rheinland Group Number of test laboratory Number of test report K 708 2012 T1 Flue gas values Wood Flue gas mass flow [g/s] 20.3 Flue gas mass flow [g/s] 320 Necessary flue draught [Pa] 11 Further important characteristics of the appliance Suitability for installation to a shared flue¹⁾ Connectivity to the central heating system General technical approval for room sealed operation

On behalf of the manufacturer, the HKI Industrieverband e.V. hereby confirms compliance with the respective requirements* in accordance with 1.BImSchV. The type test report of the fireplace has been submitted to the HKI Industrieverband e.V.

¹⁾ For unsealed operation it is possible to install the appliances to a shared flue system (please see installation manual).

^{*}A green check mark with a "1" indicates that the requirements of the 1st BImSchV are fulfilled, a green check mark with a "2" indicates that the 2nd level of the 1st BImSchV is fulfilled. A yellow check mark shows that the transitional regulation of the 1st BImSchV is fulfilled and a red line means that the 1st BImSchV is not fulfilled.

rm : Inset appliance with flat-layer firing	Evaluation
1.BlmSchV	Stufe 2
ustrian regulation referred to Art 15a B-VG	✓
Swiss clean air act	✓
Crédit d'impôt à la transition énergétique	•

Evaluation of emission data and efficiency Lignite briquettes		
Norm : Inset appliance with flat-layer firing	Evaluation	
D - 1.BlmSchV		



No symbol means that there are no requirements.

No measuring values are available for this fuel, operation with this fuel is not permitted

Here you will find further information

No information/unknown