

## Appliances properties: Supra S.A. - 258 D - Marke Worldkamin

Master data	
Date of entry	Feb 26, 2008
Manufacturer	Supra S.A.
Model	258 D
Product code	Marke Worldkamin
Nominal heat output [kW]	12
Continuous burning appliance	_
Type test standard	DIN 18895
Year of testing	1990
Test laboratory	RWE Rheinbraun AG
Number of test laboratory	4.1
Number of test report	RBW-VF 1-Hn 41/89

Flue	gas	values
1 100	guo	valuoo

	Wood	
Flue gas mass flow [g/s]	12	
Flue gas mass flow [g/s]	300	
Necessary flue draught [Pa]	12	

Further important characteristics of the appliance

Suitability for installation to a shared  $flue^{1)}$ 



Connectivity to the central heating system

## General technical approval for room sealed operation

On behalf of the manufacturer, the HKI Industrieverband e.V. hereby confirms compliance with the respective requirements\* in accordance with 1.BImSchV. The type test report of the fireplace has been submitted to the HKI Industrieverband e.V.

<sup>1)</sup> For unsealed operation it is possible to install the appliances to a shared flue system (please see installation manual).

On behalf of the manufacturer, the HKI Industrieverband e.V. hereby confirms compliance with the respective requirements\* in accordance with 1.BImSchV. The type test report of the fireplace has

<sup>\*</sup> A green check mark with a "1" indicates that the requirements of the 1st BImSchV are fulfilled, a green check mark with a "2" indicates that the 2nd level of the 1st BImSchV is fulfilled. A yellow check mark shows that the transitional regulation of the 1st BImSchV is fulfilled and a red line means that the 1st BImSchV is not fulfilled.

## Norm: Inset appliances (with closed firedoor) D - 1.BImSchV According to the transitional rule §26 the appliance can be used until 31.12.2020 A - Austrian regulation referred to Art 15a B-VG CH - Swiss clean air act F - Crédit d'impôt à la transition énergétique

Evaluation of emission data and efficiency Wood

## Evaluation of emission data and efficiency Lignite briquettes Norm: Inset appliances (with closed firedoor) Evaluation D - 1.BImSchV According to the transitional rule §26 the appliance can be used until 31.12.2020 A - Austrian regulation referred to Art 15a B-VG CH - Swiss clean air act



No symbol means that there are no requirements.

No measuring values are available for this fuel, operation with this fuel is not permitted

Here you will find further information

No information/unknown