

## Appliances properties: Wodtke GmbH - HK 05A1 mit Nachheizkasten

Master data Date of entry Jan 14, 2009 Manufacturer Wodtke GmbH Model HK 05A1 mit Nachheizkasten Nominal heat output [kW] 11 Continuous burning appliance Type test standard **DIN 18895** 1997 Year of testing **Test laboratory** RWE Rheinbraun AG Number of test laboratory 4.1 Number of test report RB BF1-Hn 49/97 Flue gas values Wood Flue gas mass flow [g/s] 14 Flue gas mass flow [g/s] 220 Necessary flue draught [Pa] 14 Further important characteristics of the appliance

Suitability for installation to a shared flue<sup>1)</sup>

Connectivity to the central heating system

General technical approval for room sealed operation

On behalf of the manufacturer, the HKI Industrieverband e.V. hereby confirms compliance with the respective requirements\* in accordance with 1.BImSchV. The type test report of the fireplace has been submitted to the HKI Industrieverband e.V.

<sup>1)</sup> For unsealed operation it is possible to install the appliances to a shared flue system (please see installation manual).

<sup>\*</sup>A green check mark with a "1" indicates that the requirements of the 1st BImSchV are fulfilled, a green check mark with a "2" indicates that the 2nd level of the 1st BImSchV is fulfilled. A yellow check mark shows that the transitional regulation of the 1st BImSchV is fulfilled and a red line means that the 1st BImSchV is not fulfilled.

## Norm : Inset appliance with flat-layer firing Evaluation D - 1.BImSchV ✓ F - Crédit d'impôt à la transition énergétique —

## Evaluation of emission data and efficiency Lignite briquettes Norm : Inset appliance with flat-layer firing Evaluation

D - 1.BImSchV

According to the transitional rule §26 the appliance can be used until 31.12.2024



No symbol means that there are no requirements.

No measuring values are available for this fuel, operation with this fuel is not permitted

Here you will find further information

No information/unknown