

Appliances properties: Hase Kaminofenbau GmbH - Nizza

Master data		
Date of entry	Nov 15, 2011	
Manufacturer	Hase Kaminofenbau GmbH	
Model	Nizza	
Nominal heat output [kW]	5	
Continuous burning appliance	_	
Type test standard	DIN 18891	
Year of testing	1997	
Test laboratory	RWE Rheinbraun AG	
Number of test laboratory	4.1	
Number of test report	RB BF1-Hn 1063	
Flue gas values		
		Wood
Flue gas mass flow [g/s]		6
Flue gas mass flow [g/s]		330
Necessary flue draught [Pa]		11
Further important characteristics of the appliance		
Suitability for installation to a shared flue ¹⁾		_
Connectivity to the central heating system		_

¹⁾ For unsealed operation it is possible to install the appliances to a shared flue system (please see installation manual).

General technical approval for room sealed operation

On behalf of the manufacturer, the HKI Industrieverband e.V. hereby confirms compliance with the respective requirements* in accordance with 1.BImSchV. The type test report of the fireplace has been submitted to the HKI Industrieverband e.V.

^{*} A green check mark with a "1" indicates that the requirements of the 1st BImSchV are fulfilled, a green check mark with a "2" indicates that the 2nd level of the 1st BImSchV is fulfilled. A yellow check mark shows that the transitional regulation of the 1st BImSchV is fulfilled and a red line means that the 1st BImSchV is not fulfilled.

Norm DIN EN 13240 (Intermittent burning): Roomheater with flat-layer firing D - 1.BImSchV F - Crédit d'impôt à la transition énergétique Evaluation Evaluation F - Crédit d'impôt à la transition énergétique

Evaluation of emission data and efficiency Lignite briquettes

Norm DIN EN 13240 (Intermittent burning): Roomheater with flat-layer firing

Evaluation

D - 1.BImSchV





No symbol means that there are no requirements.

No measuring values are available for this fuel, operation with this fuel is not permitted

Here you will find further information

No information/unknown