

Appliances properties: Willach KG - Jupiter VII X

Master data

Date of entryOct 14, 2014ManufacturerWillach KGModelJupiter VII X

Continuous burning appliance

Thermal output 228526 kJ

Type test standard DIN EN 15250

Year of testing 2011

Test laboratory RRF Rhein-Ruhr-Feuerstättenprüfstelle GmbH

Number of test laboratory 2

Number of test report RRF - 50 11 2650, Bauartzulassung Z-43.12-150

1) For unsealed operation it is possible to install the appliances to a shared flue system (please see installation manual).



Flue gas values

	Wood	
Flue gas mass flow [g/s]	14.9	
Necessary flue draught [Pa]	12	

Further important characteristics of the appliance

Suitability for installation to a shared flue 1)



Connectivity to the central heating system

General technical approval for room sealed operation

On behalf of the manufacturer, the HKI Industrieverband e.V. hereby confirms compliance with the respective requirements* in accordance with 1.BImSchV. The type test report of the fireplace has

been submitted to the HKI Industrieverband e.V.

* A green check mark with a "1" indicates that the requirements of the 1st BImSchV are fulfilled, a green check mark with a "2" indicates that the 2nd level of the 1st BImSchV is fulfilled. A yellow check mark shows that the transitional regulation of the 1st BImSchV is fulfilled and a red line means that the 1st BImSchV is not fulfilled.

Evaluation of emission data and efficiency Wood

Norm : Slow heat release appliances	Evaluation
D - 1.BImSchV	Stufe 2
A - Austrian regulation referred to Art 15a B-VG	✓
CH - Swiss clean air act	✓
F - Crédit d'impôt à la transition énergétique	4

Evaluation of emission data and efficiency Lignite briquettes

Norm : Slow heat release appliances	Evaluation
D - 1.BlmSchV	ļ



No symbol means that there are no requirements.

No measuring values are available for this fuel, operation with this fuel is not permitted

Here you will find further information

No information/unknown