

Appliances properties: Oranier Heiztechnik GmbH - 5611-7 Domo - 5616 70

Master data

Date of entry

Manufacturer

Model

Product code

Nominal heat output [kW]

Declared nominal space heating output [kW]

Continuous burning appliance

Type test standard

Year of testing

Test laboratory

Number of test laboratory

Number of test report

Oct 15, 2010

Oranier Heiztechnik GmbH

5611-7 Domo

5616 70

7

7

DIN EN 13240

2009

Strojirensky Zkusebni Ustav s.p.

19

30-10121



Flue gas values

	Wood	
Flue gas mass flow [g/s]	10	
Flue gas mass flow [g/s]	350	
Necessary flue draught [Pa]	11	

Further important characteristics of the appliance

Suitability for installation to a shared flue 1)



Connectivity to the central heating system

General technical approval for room sealed operation

On behalf of the manufacturer, the HKI Industrieverband e.V. hereby confirms compliance with the respective requirements* in accordance with 1.BImSchV. The type test report of the fireplace has been submitted to the HKI Industrieverband e.V.

*A green check mark with a "1" indicates that the requirements of the 1st BImSchV are fulfilled, a green check mark with a "2" indicates that the 2nd level of the 1st BImSchV is fulfilled. A yellow check mark shows that the transitional regulation of the 1st BImSchV is fulfilled and a red line means that the 1st BImSchV is not fulfilled.

¹⁾ For unsealed operation it is possible to install the appliances to a shared flue system (please see installation manual).

Stufe 1 Grandfathering
✓

Evaluation of emission data and efficiency Wood

Evaluation of emission data and efficiency Lignite briquettes	
orm DIN EN 13240 (Intermittent burning): Roomheater with flat-layer firing	Evaluation
	•



No symbol means that there are no requirements.

No measuring values are available for this fuel, operation with this fuel is not permitted

Here you will find further information

No information/unknown