

## Appliances properties: Buderus, Bosch Thermotechnik GmbH - 120

Master data	
Date of entry	Jun 4, 2011
Manufacturer	Buderus, Bosch Thermotechnik GmbH
Model	120
Nominal heat output [kW]	5.6
Continuous burning appliance	_
Type test standard	DIN 18892
Year of testing	0
Further important characteristics of the appliance	
Suitability for installation to a shared flue <sup>1)</sup>	_
Connectivity to the central heating system	_
General technical approval for room sealed opera	tion
1) For unsealed operation it is possible to install the appliances to a	shared flue system (please see installation manual).

On behalf of the manufacturer, the HKI Industrieverband e.V. hereby confirms compliance with the respective requirements\* in accordance with 1.BImSchV. The type test report of the fireplace has been submitted to the HKI Industrieverband e.V.


## Evaluation of emission data and efficiency Wood Norm: Inset appliance with flat-layer firing **Evaluation** D - 1.BImSchV According to the transitional rule §26 the appliance can be used until 31.12.2014

## Evaluation of emission data and efficiency Lignite briquettes

F - Crédit d'impôt à la transition énergétique

Norm: Inset appliance with flat-layer firing **Evaluation** 

<sup>\*</sup>A green check mark with a "1" indicates that the requirements of the 1st BImSchV are fulfilled, a green check mark with a "2" indicates that the 2nd level of the 1st BImSchV is fulfilled. A yellow check mark shows that the transitional regulation of the 1st BImSchV is fulfilled and a red line means that the 1st BImSchV is not fulfilled.



No symbol means that there are no requirements.

No measuring values are available for this fuel, operation with this fuel is not permitted

Here you will find further information